

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An electric motor driven hand-held tool comprising a tool housing within which is located a motor, an integrated switch unit (6), the switch unit including an electronic motor control unit (8), a first manually operable switch member (4) located adjacent to the integrated switch unit and operatively connected to the motor control unit and to which the motor control unit is responsive to power the motor, and a second manually operable switch member (14) operatively connected to the motor control unit via an actuator (10) and to which the control unit is responsive to drive the motor in one of a selected forward and reverse direction, characterised in that the second manually operable switch member (14) is located remotely from the switch unit (6) on an upward facing portion of the tool housing which can be seen by a user of the tool during normal operation of the tool, and a linkage arrangement (16) is moveably mounted within the tool housing for moving the actuator (10) in response to a manual positioning of the second manually operable switch member (14).

2. (Cancelled)

3. (Cancelled)

4. (Currently Amended) An electric motor driven hand-held tool according to claim 1 wherein the ~~second manually operable switch member (14) is located on an upper facing face of the tool housing and the~~ first manually operable switch member (4) is located on a downwardly facing surface of the tool housing ~~and the switch unit (6) is located adjacent the first manually operable switch member.~~

5. (Previously Presented) An electric motor driven hand-held tool according to claim 1 wherein the linkage (16) is pivotably mounted within the tool housing so that manual actuation of the second manually operable switch member (14) causes the linkage to pivot and to actuate the actuator (10).

6. (Previously Presented) An electric motor driven hand-held tool according to claim 5 wherein the linkage (16) is pivotally mounted on a motor housing portion (3) of the tool housing.

7. (Previously Presented) An electric motor driven hand-held tool according to claim 6 wherein the linkage (16) is pivotably mounted on a closed end of the motor housing (3), which motor housing end is adjacent to an end of the motor.

8. (Previously Presented) An electric motor driven hand-held tool according to claim 7 wherein the closed end of the motor housing (3) is the rearward end of the motor housing.

9. (Previously Presented) An electric motor driven hand-held tool according to claim 6 wherein the pivot axis of the linkage (16) is parallel to the longitudinal axis of the motor.

10. (Previously Presented) An electric motor driven hand-held tool according to claim 6 wherein the linkage (16) is formed with a central annular portion (18) which is pivotable about a boss (24) formed on the motor housing (3).

11. (Previously Presented) An electric motor driven hand-held tool according to claim 6 wherein the motor housing is a jam pot housing (3) including a closed end and an opposite open end.

12. (Previously Presented) An electric motor driven hand-held tool according to claim 6 and further including a fixing boss (34) extending from the motor housing (3), and a rear handle portion (2) of the tool housing, and wherein the rear handle portion is

fixed to the motor housing (3) via a fixing which engages the fixing boss (34), and the fixing boss (34) is engageable with the linkage (16) to limit movement of the linkage (16) within the tool housing.

13. (Previously Presented) An electric motor driven hand-held tool according to claim 5 and further including a first arm (20) extending from the linkage, and second manually operable switch member (14) is located on the first arm.

14. (Previously Presented) An electric motor driven hand-held tool according to claim 13 and further including a second arm (22) extending from the linkage, and the second arm (22) engages the actuator (10).

15. (Previously Presented) An electric motor driven hand-held tool according to claim 1 wherein the first manually operable switch member (4) is a trigger switch.

16. (Previously Presented) An electric motor driven hand-held tool according to claim 1 wherein the first manually operable switch member (4) and switch unit (6) are arranged such that when the first manually operable switch member (4) is acted on by a user of the tool so as to power the motor, the first manually operable switch member (4) holds the actuator (10) against movement by the linkage (16).

17. (Previously Presented) An electric motor driven hand-held tool comprising:

- a tool housing including a motor housing portion, an upper facing portion, a lower facing portion, and an interior circular boss;

- a handle, extending downward from the lower facing portion of the tool housing;

- a motor located within the motor housing portion and defining a longitudinal axis;

- an integrated switch unit including an electronic motor control unit and located in the handle;

a first manually operable switch member projecting through handle and operatively connected to the motor control unit, and whereby a tool user controls the speed of the motor;

a second manually operable switch member projecting through the upward facing portion of the motor housing and whereby a tool user controls the direction of the motor, and

a linkage arrangement pivotably mounted on the interior circular boss within the tool housing, the linkage operatively connecting the second manually operable switch member to the motor control unit.